



HP096 is a hard tag made of PVC, a flexible and ductile thermoplastic with elevated resistance to high and low temperatures. Rectangular in shape, it measures 100 mm x 24.5 mm x 1.5 mm and weighs 5 grams. **It can be applied to non-metal surfaces and to metal surfaces on request. It is equipped with two holes for anchoring to objects**

using screws. White in colour and available in **LF, HF and UHF**, it can be customised with a logo using offset or pad printing, while numbering can be applied using laser or inkjet technology.

MARKETS

With an **IP67** protection rating, which ensures resistance to water,

the tag is also sealed against smoke and dust. HP096 can be used for **asset and waste management.**



frequency 125 kHz

RFID features

| Chip | Memory | ISO Standard |
|------------------|--------------------------|-------------------|
| EM4100 or GK4100 | 0 bytes - UID: 8 bytes | - |
| EM4102 | 0 bytes - UID: 8 bytes | - |
| EM4200 | 0 bytes - UID: 8 bytes | ISO 11784 / 11785 |
| EM4550 or TITAN | 128 bytes - UID: 8 bytes | ISO 11784 / 11785 |
| EM4305 | 64 bytes - UID: 4 bytes | ISO 11784 / 11785 |
| ATA5577 or T5567 | 36 bytes - UID: 8 bytes | ISO 11784 / 11785 |
| Q5 or 5555 | 33 bytes - UID: 8 bytes | ISO 11784 / 11785 |
| HITAG1 | 256 bytes | - |
| HITAG2 | 32 bytes | ISO 11784 / 11785 |
| HITAG S 2048 | 256 bytes - UID: 4 bytes | ISO 11784 / 11785 |
| HITAG S 256 | 32 bytes - UID: 4 bytes | ISO 11784 / 11785 |
| SIC279 | 16/24 bytes | ISO 11784 / 11785 |
| S5777 | 28 bytes - UID: 8 bytes | ISO 15693 |



frequency 13.56 MHz

RFID features

| Chip | Memory | ISO Standard | NFC Standard |
|-----------------------------------|---------------------------|--------------|--|
| RF81 | 1024 bytes - UID: 4 bytes | ISO 14443 A | Not supported by majority of NFC devices |
| FM11RF08 | 1024 bytes - UID: 4 bytes | ISO 14443 A | Not supported by majority of NFC devices |
| RF005 | 64 bytes - UID: 7 bytes | ISO 14443 A | Not supported by majority of NFC devices |
| RF32 | 4096 bytes - UID: 4 bytes | ISO 14443 A | Not supported by majority of NFC devices |
| MIFARE CLASSIC 1K EV1 S50 | 1024 bytes - UID: 4 bytes | ISO 14443 A | Not supported by majority of NFC devices |
| MIFARE CLASSIC 1K EV1 S50 7 BYTES | 1024 bytes - UID: 7 bytes | ISO 14443 A | Not supported by majority of NFC devices |
| MIFARE CLASSIC 4K EV1 S70 | 4096 bytes - UID: 4 bytes | ISO 14443 A | Type 2 - tag compliant |
| MIFARE ULTRALIGHT EV1-1 | 48 bytes - UID: 7 bytes | ISO 14443 A | Type 2 - tag compliant |
| MIFARE ULTRALIGHT EV1-2 | 128 bytes - UID: 7 bytes | ISO 14443 A | Type 2 - tag compliant |
| MIFARE ULTRALIGHT C | 144 bytes - UID: 7 bytes | ISO 14443 A | Type 2 - tag compliant |
| MIFARE DESFIRE EV1 2K | 2048 bytes - UID: 7 bytes | ISO 14443 A | Type 4 - tag compliant |
| MIFARE DESFIRE EV1 4K | 4096 bytes - UID: 7 bytes | ISO 14443 A | Type 4 - tag compliant |
| MIFARE DESFIRE EV1 8K | 8192 bytes - UID: 7 bytes | ISO 14443 A | Type 4 - tag compliant |
| MIFARE DESFIRE EV2 2K | 2048 bytes - UID: 7 bytes | ISO 14443 A | Type 4 - tag compliant |
| MIFARE DESFIRE EV2 4K | 4096 bytes - UID: 7 bytes | ISO 14443 A | Type 4 - tag compliant |
| MIFARE DESFIRE EV2 8K | 8192 bytes - UID: 7 bytes | ISO 14443 A | Type 4 - tag compliant |
| MIFARE DESFIRE EV3 2K | 2048 bytes - UID: 7 bytes | ISO 14443 A | Type 4 - tag compliant |

| | | | |
|-------------------------|---|-------------------------|--|
| MIFARE DESFIRE EV3 4K | 4096 bytes - UID: 7 bytes | ISO 14443 A | Type 4 - tag compliant |
| MIFARE DESFIRE EV3 8K | 8192 bytes - UID: 7 bytes | ISO 14443 A | Type 4 - tag compliant |
| MIFARE DESFIRE LIGHT | 640 bytes - UID: 7 bytes | ISO 14443 A | Type 4 - tag compliant |
| MIFARE PLUS SE | 1024 bytes - UID: 7 bytes | ISO 14443 A | Not supported by majority of NFC devices |
| MIFARE PLUS 2K | 2048 bytes - UID: 7 bytes | ISO 14443 A | Not supported by majority of NFC devices |
| MIFARE PLUS 4K | 4096 bytes - UID: 7 bytes | ISO 14443 A | Not supported by majority of NFC devices |
| MIFARE PLUS X 2K | 2048 bytes - UID: 7 bytes | ISO 14443 A | Not supported by majority of NFC devices |
| MIFARE PLUS X 4K | 4096 bytes - UID: 7 bytes | ISO 14443 A | Not supported by majority of NFC devices |
| MIFARE PLUS EV2 2K | 2048 bytes - UID: 7 bytes | ISO 14443 A | Not supported by majority of NFC devices |
| MIFARE PLUS EV2 4K | 4096 bytes - UID: 7 bytes | ISO 14443 A | Not supported by majority of NFC devices |
| ATC1024-MV110 | 944 bytes - UID: 8 bytes | ISO 15693 | Not supported by majority of NFC devices |
| ATC256-MV410 | 224 bytes - UID: 8 bytes | ISO 15693 | Not supported by majority of NFC devices |
| ATC4096-MP311 | 4096 bytes - UID: 7 bytes | ISO 14443 A | Not supported by majority of NFC devices |
| CTC4096-MP410 | 2984 bytes (advant) / 1002 bytes (prime) - UID: 4/7 bytes | ISO 14443 A | Not supported by majority of NFC devices |
| CTC4096-MM410 | 2984 bytes (advant) / 1002 bytes (prime) - UID: 4/7 bytes | ISO 15693 - ISO 14443 A | Not supported by majority of NFC devices |
| EM4233 | 256 bytes - UID: 8 bytes | ISO 15693 | Not supported by majority of NFC devices |
| ICODE SLI-S | 256 bytes - UID: 8 bytes | ISO 15693 | Type 5 - tag compliant |
| ICODE SLIX | 128 bytes - UID: 8 bytes | ISO 15693 | Type 5 - tag compliant |
| ICODE SLIX2 | 316 bytes - UID: 8 bytes | ISO 15693 | Not supported by majority of NFC devices |
| ICODE SLIX-S | 160 bytes - UID: 8 bytes | ISO 15693 | Type 5 - tag compliant |
| ICODE DNA | 252 bytes - UID: 8 bytes | ISO 15693 | Type 5 - tag compliant |
| MIM1024/PRIME | 1024 bytes | ISO 14443 A | Not supported by majority of NFC devices |
| MIM256/PRIME | 256 bytes | ISO 14443 A | Not supported by majority of NFC devices |
| NTAG210 | 48 bytes - UID: 7 bytes | ISO 14443 A | Type 2 - tag compliant |
| NTAG212 | 128 bytes - UID: 7 bytes | ISO 14443 A | Type 2 - tag compliant |
| NTAG213 | 144 bytes - UID: 7 bytes | ISO 14443 A | Type 2 - tag compliant |
| NTAG215 | 504 bytes - UID: 7 bytes | ISO 14443 A | Type 2 - tag compliant |
| NTAG216 | 888 bytes - UID: 7 bytes | ISO 14443 A | Type 2 - tag compliant |
| NTAG213 TT (TAG TAMPER) | 144 bytes - UID: 7 bytes | ISO 14443 A | Type 2 - tag compliant |
| NTAG413 DNA | 32/128 bytes - UID: 7 bytes | ISO 14443 A | Type 4 - tag compliant |
| NTAG424 DNA | 416 bytes - UID: 7 bytes | ISO 14443 A | Type 4 - tag compliant |
| ST25TV02K | 250 bytes - UID: 8 bytes | ISO 15693 | Type 5 - tag compliant |
| ST25TB512 | 64 bytes - UID: 8 bytes | ISO 14443 B | Type 4 - tag compliant |
| ST25TB04K | 512 bytes - UID: 8 bytes | ISO 14443 B | Type 4 - tag compliant |

| | | | |
|------------|---------------------------|-------------|--|
| ST25TB02K | 256 bytes - UID: 8 bytes | ISO 14443 B | Type 4 - tag compliant |
| TAG-IT 256 | 32 bytes - UID: 8 bytes | ISO 15693 | Type 5 - tag compliant |
| TAG-IT 2K | 256 bytes - UID: 8 bytes | ISO 15693 | Type 5 - tag compliant |
| MB89R118 | 2000 bytes - UID: 8 bytes | ISO 15693 | Not supported by majority of NFC devices |



European frequency (EU) 868 MHz - US frequency 920 MHz

RFID features

| Chip | Memory | ISO Standard |
|--------------|--|----------------------------------|
| HIGGS 3 | 64 bytes - TID: 8 bytes - EPC: 60 bytes | ISO 18000-6C / EPC Class 1 Gen 2 |
| HIGGS 3 US | 64 bytes - TID: 8 bytes - EPC: 60 bytes | ISO 18000-6C / EPC Class 1 Gen 2 |
| HIGGS 4 | 16 bytes - TID: 8 bytes - EPC: 16 bytes | ISO 18000-6C / EPC Class 1 Gen 2 |
| HIGGS 4 US | 16 bytes - TID: 8 bytes - EPC: 16 bytes | ISO 18000-6C / EPC Class 1 Gen 2 |
| HIGGS 9 | 86 bytes - TID: 6 bytes - EPC: 62 bytes | ISO 18000-6C / EPC Class 1 Gen 2 |
| UCODE 7 | 0 bytes - TID: 12 bytes - EPC: 16 bytes | EPC Class 1 Gen 2 |
| UCODE 7 US | 0 bytes - TID: 12 bytes - EPC: 16 bytes | EPC Class 1 Gen 2 |
| UCODE 8 | 0 bytes - TID: 12 bytes - EPC: 16 bytes | EPC Class 1 Gen 2 |
| UCODE 8 US | 0 bytes - TID: 12 bytes - EPC: 16 bytes | EPC Class 1 Gen 2 |
| UCODE 8 M | 4 bytes - TID: 12 bytes - EPC: 12 bytes | EPC Class 1 Gen 2 |
| UCODE 9 | 0 bytes - TID: 12 bytes - EPC: 12 bytes | EPC Gen 2 V2 |
| UCODE G2IL | 0 bytes - TID: 8 bytes - EPC: 16 bytes | EPC Class 1 Gen 2 |
| UCODE G2IM | 80 bytes - TID: 12 bytes - EPC: 32 bytes | EPC Class 1 Gen 2 |
| UCODE DNA | 3072 bytes - TID: 12 bytes - EPC: 56 bytes | ISO 29167-10 / EPC Gen 2 V2 |
| UCODE CITY | 128 bytes - TID: 12 bytes - EPC: 28 bytes | ISO 29167-10 / EPC Gen 2 V2 |
| UCODE TRACK | 32 bytes - TID: 12 bytes - EPC: 56 bytes | ISO 29167-10 / EPC Gen 2 V2 |
| MONZA R5 | 0 bytes - TID: 16 bytes - EPC: 16 bytes | ISO 18000-6C / EPC Gen 2 |
| MONZA R6 | 0 bytes - TID: 12 bytes - EPC: 12 bytes | ISO 18000-63 / EPC Gen 2 V2 |
| MONZA R6 US | 0 bytes - TID: 12 bytes - EPC: 12 bytes | ISO 18000-63 / EPC Gen 2 V2 |
| MONZA R6A | 0 bytes - TID: 12 bytes - EPC: 12 bytes | ISO 18000-63 / EPC Gen 2 V2 |
| MONZA R6B | 0 bytes - TID: 12 bytes - EPC: 12 bytes | ISO 18000-63 / EPC Gen 2 V2 |
| MONZA R6P | 8 bytes - TID: 12 bytes - EPC: 16 bytes | ISO 18000-63 / EPC Gen 2 V2 |
| MONZA R6P US | 8 bytes - TID: 12 bytes - EPC: 16 bytes | ISO 18000-63 / EPC Gen 2 V2 |
| MONZA 4D | 4 bytes - TID: 12 bytes - EPC: 16 bytes | ISO 18000-63 / EPC Class 1 Gen 2 |
| MONZA 4D US | 4 bytes - TID: 12 bytes - EPC: 16 bytes | ISO 18000-63 / EPC Class 1 Gen 2 |
| MONZA 4E | 16 bytes - TID: 12 bytes - EPC: 62 bytes | ISO 18000-63 / EPC Class 1 Gen 2 |
| MONZA 4QT | 64 bytes - TID: 12 bytes - EPC: 16 bytes | ISO 18000-63 / EPC Class 1 Gen 2 |
| MONZA M730 | 0 bytes - TID: 12 bytes - EPC: 16 bytes | ISO 18000-63 / EPC Gen 2 V2 |
| MONZA M750 | 4 bytes - TID: 12 bytes - EPC: 12 bytes | ISO 18000-63 / EPC Gen 2 V2 |
| KX2005XG-B | 164 bytes - UID: 24 bytes - EPC: 30 bytes | ISO 18000-6C / EPC Class 1 Gen 2 |
| HIGGS-EC | 16 bytes- UID: 6 bytes - EPC: 16 bytes | ISO 18000-63 / EPC Gen 2 V1. 2.0 |
| HIGGS-EC US | 16 bytes- UID: 6 bytes - EPC: 16 bytes | ISO 18000-63 / EPC Gen 2 V1. 2.0 |

Technical specifications

| | |
|--|---|
| Application | Metal (on request) and non-metal surfaces |
| IP rating | 67 |
| Dimensions | 100 x 24.5 x 1.5 mm - \varnothing hole 4 mm |
| Material | PVC |
| Weight | 5 g |
| Application method | Screws or adhesive |
| Operation and storage temperature | -35°C - +75°C |

Customisation

| | |
|--------------------------|-------------------------|
| Colour | White |
| Type of printing | Offset and pad printing |
| Type of numbering | Laser, inkjet |

