



HT067 is an RFID hard tag made of engineering plastic, whose high performance makes it resistant to mechanical impacts, chemical reagents and both high and low temperatures.

Rectangular in shape, HT067 weighs approximately 19 grams and

measures 54 mm x 36 mm x 12.5 mm. **Designed for application on dense metal surfaces** using an adhesive backing or screws, it is available in **European and US UHF with the UCODE 8 chip.**

Yellow in colour, this tag can be customised using laser technology.

#### MARKETS

Its IP68 rating ensures resistance to water and dust. It is ideal for **asset-management projects, inventory management and industrial automation.**



European frequency (EU) 868 MHz - US frequency 920 MHz

## RFID features

Chip	Memory	ISO Standard
UCODE 8	0 bytes - TID: 12 bytes - EPC: 16 bytes	EPC Class 1 Gen 2
UCODE 8 US	0 bytes - TID: 12 bytes - EPC: 16 bytes	EPC Class 1 Gen 2

## Technical specifications

Application	Metal surfaces
IP rating	68
Dimensions	54 x 36 x 12.5 mm
Material	Engineering plastic
Weight	19.5 g
Application method	Adhesive or screws
Operation and storage temperature	-40°C ~ +85°C

## Customisation

Colour	Yellow
Type of printing and numbering	Laser technology

