



HT071 is an RFID hard tag made of nylon, a material which gives rigidity, compressive strength and dimensional stability. Rectangular in shape - **measuring 78 x 21 x 11 mm** - this robust RFID tag is **designed to be applied to even narrow metal objects by screwing**.

Available **in UHF frequency** (both European and US) **with the UCODE 8 chip**, in black, it can be customised with a logo by pad printing and laser printing, while serialisation is done by laser technique.

MARKETS

Thanks to its IP68 rating, this tag is highly resistant to water and powder and it can be used in **Logistics and industrial asset management**.



European frequency (EU) 868 MHz - US frequency 920 MHz

RFID features

Chip	Memory	ISO Standard
UCODE 8	0 bytes - TID: 12 bytes - EPC: 16 bytes	EPC Class 1 Gen 2
UCODE 8 US	0 bytes - TID: 12 bytes - EPC: 16 bytes	EPC Class 1 Gen 2

Technical specifications

Application	Metal surfaces
IP rating	68
Dimensions	78 x 21 x 11 mm
Material	Nylon
Application method	Adhesive/screws
Operation temperature	-40°C ~ +85°C
Storage temperature	-40°C ~ +120°C

Customisation

Colour	Black
Type of printing	Pad printing and laser printing
Type of numbering	Laser printing

